

Series: 550, **551**, 551D, 552, 554, 557, 550H, 551H

SERIES551

Twin wheel swivel castor
with total lock or wheel lock



RAL
7004

RAL
9002

Ø
150 mm

Technical specifications

- Polyamid casing
- combined plain ball bearing swivel (ø 65, ø 75 and ø 100 mm)
- Precision ball bearing swivel (ø 125 and ø 150 mm)
- Wheel lock (ø 65 mm)
- Total lock (> ø 65 mm)
- non-marking, grey polyurethane tyres (TPU)

Available options / equipment

- other mounting options
- further RAL colours (minimum order quantity required)
- grey polyamide plain bearing wheels (ø 65 and ø 75 mm)
- Precision ball bearing swivel (ø 100 mm)
- Cable guard from ø 100 - ø 150 mm
- Wheel lock from ø 75 mm

SERIES551													
	M10x15	65	14	79	20	68	70	4.RUL0.DGA0	4.RUN0.DGC0				
	M10x15	75	18	90	23	75	70	4.S5A0.DLA0	4.S5C0.DLC0	4.RLA0.DJA0	4.RLC0.DJC0		
	M10x15	100	20	119	31	105	70	4.R4A0.DHA0		4.R4B0.DMA0	4.R4C0.DNC0		
	M12x15	65	14	81	20	68	70	4.RUS0.DGA0	4.RUU0.DGC0				
	M12x15	75	18	92	23	75	70	4.S5T0.DLA0	4.S5V0.DLC0	4.RLF0.DJA0	4.RLH0.DJC0		
	M12x15	100	20	121	31	105	100	4.R4T0.DHA0		4.R400.DMA0	4.R4V0.DNC0		
	M12x25	125	20	149	40	132	110			4.TEA0.DPA0	4.TEC0.DPC0		
	M12x25	150	20	186	52	156	110			4.SQA0.DQH0	4.SQB0.DQJ0		
	55x55	65	14	79	20	68	70	4.RWA0.DGA0	4.RWC0.DGC0				
	55x55	75	18	95	23	75	70	4.S7A0.DLA0	4.S7C0.DLC0	4.RLW0.DJA0	4.RLY0.DJC0		
	55x55	100	20	124	31	105	100	4.R5A0.DHA0		4.R5D0.DMA0	4.R5C0.DNC0		
	77x67	125	20	154	40	132	110			4.TGA0.DPA0	4.TGC0.DPC0		
	77x67	150	20	192	52	156	110			4.SRA0.DQH0	4.SRB0.DQJ0		
		10x34	65	14	79	20	68	70	4.RVA0.DGA0	4.RVC0.DGC0			
10x34		75	18	90	23	75	70	4.S6T0.DLA0	4.S6V0.DLC0	4.RLK0.DJA0	4.RLM0.DJC0		
10x34		100	20	119	31	105	70	4.R720.DHA0		4.R7S0.DMA0	4.R7T0.DNC0		
11x22		65	14	81	20	68	70	4.RUY0.DGA0	4.RU00.DGC0				
11x22		75	18	92	23	75	70	4.S6Y0.DLA0	4.S6R0.DLC0	4.RLP0.DJA0	4.RLR0.DJC0		
11x22		100	20	121	31	105	100	4.R5F0.DHA0		4.R7Q0.DMA0	4.R7R0.DNC0		
16x26,5		125	20	145	40	132	110			4.TH80.DPA0	4.TF90.DPC0		
	18,65x25	150	20	190	52	156	110			4.SR50.DQH0	4.SR60.DQJ0		
	18x45	125	20	145	40	132	110			4.TF01.DPA0	4.TG01.DPC0		
	18x45	150	20	186	40	156	110			4.SR80.DQH0	4.SR70.DQJ0		
all measurements in mm							kg						