

Series: 550, 551, 551D, **552**, 554, 557, 550H, 551H

SERIES 552

Twin wheel swivel castor
with directional lock



RAL
7004



Technical specifications

- Polyamid casing
- combined plain ball bearing swivel (ø 100 mm)
- Precision ball bearing swivel (ø 125 mm)
- non-marking, grey polyurethane tyres (TPU)

Available options / equipment

- other mounting options
- further RAL colours (minimum order quantity required)
- Precision ball bearing swivel (ø 100 mm)
- Cable guard from ø 100
- Label for directional lock and brake pedal

**By using a plain stem or screw fitting the castor has to be aligned in travel direction.
We recommend a plate fitting. Please contact STEINCO.**

SERIES 552											
	M10x15	100	20	119	31	105	70			4.R8H0.DMA0	4.R8J0.DNC0
	M12x15	100	20	121	31	105	100			4.R8F0.DMA0	4.R8G0.DNC0
	M12x25	125	20	149	40	132	110			4.TLA0.DPA0	4.TLC0.DPC0
	55x55	100	20	124	31	105	100			4.R8T0.DMA0	4.R8U0.DNC0
	77x67	125	20	154	40	132	110			4.TNA0.DPA0	4.TNC0.DPC0
	16x26,5	125	20	149	40	132	110			4.TL40.DPA0	4.TL50.DPC0
	32x50	100	20	124	31	105	100			4.R800.DMA0	4.R810.DNC0
	18x45	125	20	149	40	132	110			4.TLS1.DPA0	4.TLT1.DPC0
all measurements in mm							kg				