

Series: 558(W), 559(W)



SERIES 558/558W

Twin wheel castor

with central operating total lock



SERIES 559/559W

Twin wheel castor

with central operating total or directional lock



RAL
9002

Technical specifications

- Polyamid casing
- Precision ball bearing swivel
- quiet, smooth and positive brake performance
- 30° cam
- hexagonal eccentric position: flat in neutral position
- non-marking, grey polyurethane tyres (TPU)
- riveted axle
- no re-adjustment necessary
- washable version **W** (see table)



Available options / equipment

- other mounting options
- further RAL colours (minimum order quantity required)
- matching swivel castor see SERIES 550H/551H
- other hexagonal eccentric positions
- Cable guard
- anti-magnetic version

SERIES 558										W	W
	32x50	125	20	158	40	107	110	4.TWR0.DP30	4.TWS0.DN20	4.TJR0.DRA0	4.TJS0.DRB0
	32x50	150	20	180	52	131	150	4.SWR0.DQ20	4.SWS0.DQ30	4.SNR0.DQB0	4.SNS0.DQD0
	28x95	125	20	158	40	107	110	4.TWF0.DP30	4.TWG0.DN20	4.TJF0.DRA0	4.TJG0.DRB0
	28x95	150	20	180	52	131	150	4.SWF0.DQ20	4.SWG0.DQ30	4.SNF0.DQB0	4.SNG0.DQD0
SERIES 559										W	W
	32x50	125	20	158	40	107	110	4.TWL0.DP30	4.TWM0.DN20	4.TJL0.DRA0	4.TJM0.DRB0
	32x50	150	20	180	52	131	150	4.SWL0.DQ20	4.SWM0.DQ30	4.SNL0.DQB0	4.SNM0.DQD0
	28x95	125	20	158	40	107	110	4.TWA0.DP30	4.TWB0.DN20	4.TJA0.DRA0	4.TJB0.DRB0
	28x95	150	20	180	52	131	150	4.SWA0.DQ20	4.SWB0.DQ30	4.SNA0.DQB0	4.SNB0.DQD0
all measurements in mm							kg				